AHD-3076-ASB AHD Camera

Product photo



Main Features

- 1. By using the high performance sensor, image is clear, delicate and high performance sensor, image is clear, delicate;
- 2. Support IR-CUT dual filter switch, day and night to achieve monitoring, color is not partial color distortion;
- 3. Analog HD and AHD-M video output;
- 4. Support for OSD menu options, can be freely adjusted image, function;
- 5. The transmission distance is 500 meters;
- 6. The need to access the back-end AHD DVR;
- 7. Support the ultra low illumination;
- 8. Support automatic electronic shutter function, adapt to different monitoring environment;
- 9. Waterproof design IP66, reliability;
- 10 Million pixel HD video transmission of low cost, long distance, no delay, high efficiency, anti-jamming and easy to implement;

Technical Specification

Model	AHD-3076-ASB
Image sensor	1/4" AR0141 CMOS
Signal	AHD-M
Effective pixels	1280*720
Minimum illumination	Color 0. 1Lux @(F1.2,AGC ON),0 LUX with IR
	B/W 0. 01 Lux @ (F1.2,AGC ON),0 LUX with IR
Shutter	1/50(1/60)S~1/10,000S
IR_CUT	Support IR-CUT
Lens	3.6mm Mega pixels lens
IR Range	24 PCS ¢5 IR Leds / 20 meters IR distance
Video output	1Vp-p Composite Output(75 Ω/BNC)
Working Condition	$-10^{\circ}\text{C} \sim 60^{\circ}\text{C}$, Humidity < 90% (No condensation)
Power	DC12V±10%
Protection rade	IP66