

HED TBO-3206CF Focus Outside Adjustable IR Cameras

Feature

- 1/3" SONY CCD
- High resolution 540TVL
- OSD
- 4-9mm Lens
- $\Phi 5 \times 48$ IR LEDs
- Cable inside bracket



Specifications

| | |
|--|--|
| Model | HED TBO-3206CF |
| Pickup device | 1/3" SONY CCD |
| Effective Pixels | NTSC:768(H)*494(V),PAL:752(H)*582(V) |
| Sync system | Internal |
| Resolution | 540TVL |
| Min. Illumination <input type="checkbox"/> | 0.2Lux / F1.2, 0Lux (IR on) <input type="checkbox"/> |
| S/N | More than 48dB |
| Electronic shutter | NTSC:1/60~1/100,000,PAL:1/50~1/100,000 |
| Flickerless Mode | On/Off |
| Len | built-in adjustable lens (6~15mm) |
| Gamma | 0,45 |
| White balance | Auto (ATW,AWB,FIXED,MANUAL) <input type="checkbox"/> |
| AGC Gain Control | High / Low (6dB~40dB) <input type="checkbox"/> |
| Back Light Comp | On / Off (64AREA) <input type="checkbox"/> |
| Motion Detection | On / Off (64AREA) |
| Video Output | 1.0Vp-p/75Ohm |
| Power supply | DC12V \pm 10% |
| IR distance | 20-50m |
| Power consumption | 75mA,430mA(IR ON) |
| Operating Temp | -10 <input type="checkbox"/> to +50 <input type="checkbox"/> |
| Weight(g) | 1380 |
| Dimension | please refer to right figure |



