

STANDALONE H.264 DVR



**HED RNXX07C-S series Standalone
DVR 4//8/16ch**

Model

RN0407C-S 4 channel model
RN0807C-S 8 channel model
RN1607C-S 16 channel model

Features

1. Hi3515 CPU, H.264 Main Profile
2. High definition realtime D1 recording and 1~8channels playback
3. Standard Main and sub streams,main stream for local record and storage, sub stream for remote monitor and access
4. Genuine High definition VGA output and TV output simultaneously
5. Built-in DDNS with 3322,dyndns,myq-see and anfangbao,UPNP with auto ports mapping,to make remote access very easy
6. Support Max 2T sata HDD
7. Support 5 kinds of mobile remote monitoring
8. Support Bidirectional Talk
9. Support PAL/NTSC format and 16kinds of languages
- 10.Beautiful front panel button with LED light



Model		RN0407C-S	RN0807C-S	RN1607C-S
System	Main Processor	High performance embedded microprocessor		
	Operating System	Embedded LINUX		
	System Resources	Pentaplex function:live,recording,playback,backup & remote access		
	User Interface	GUI,on-screen menu tips		
	Control Device	Front panel,USB mouse,IR remote control		
Video	Video Standards	PAL 625 line,50 f/s;NTSC 525 line,60 f/s		
	Video Compression	H.264 main profile		
	Video Recording	D1:PAL 1f/s-25f/s NTSC 1f/s-30f/s;		
	Motion Detection	Zones:396(22*18)detection zones,Sensitivity:1-6(6 is highest) Trigger recording,PTZ movement,tour,alarm,e-mail& FTP		
	TV Output Adjustment	Adjust TV output color & display zone		
Audio	Audio Compression	G711A		

Record & Playback	Recording Mode	Manual>Alarm>Video Detection>Continuous		
	Encode	D1/HD1/CIF/QCIF, Main and sub streams		
	Encode capacity	100/120fps D1	2D1+6CIF(first 2ch D1)	400/480fps CIF
	Playback	Max 4/8/16 channels playback simultaneously, Pause,stop,rewind,fast play,slow play,next file,previous file,repeat,shuffle,backup selection		
	Search Mode	Time/Date,Alarm,Motion Detection & exact search(accurate to second)		
Storage & Backup	Space Occupation	Audio28.8MB/H Video150-200 MB/H		
	HDD Management	Hard disk hibernation technology,HDD faulty alarm & Raid(Redundancy)		
	Backup Mode	Network download/Flash stick		
Interface	Video Input	4 channel	8 channel	16 channel
	Video Output	1 channel TV output BNC,1.0Vp-p,75Ω,1 VGA output		
	Audio Input	4 channel		1 channel
	Audio Output	1 channel		
	Alarm Input	4 channel		1 channel
	Relay Output	1 channel		
	Net Interface	RJ-45 (10M/100M)		
	PTZ Control	1 RS485		
	USB Interface	2* USB2.0 port for mouse and backup		
	SD Interface	N/A		
Environmental	Hard Disk	1 SATA port(Max 2048G)		
	Power Supply	12V/4A		
	Power Output	2 x 12V for cameras and alarm sensors	N/A	
	Power Consumption	<10W		
	Working Temperature	0-55		
	Working Humidity	10%-90%		
	Atmosphere Pressure	86kpa-106kpa		
	Dimension	Packing size 390*302*130mm		
Weight	2.6kg			
Mounting	Desktop			